



AVS-Camera-KU FHD

mit integrierter IR-Beleuchtung / with integrated IR-lightning



Produktvarianten / *Product variants*

3010147	AVS-Camera-KU 40° FHD	▪ Bildwinkel 40°	▪ <i>Viewing angle 40°</i>
3810013	AVS-Camera-KU 70° FHD	▪ Bildwinkel 70°	▪ <i>Viewing angle 70°</i>
3010126	AVS-Camera-KU 90° FHD	▪ Bildwinkel 90°	▪ <i>Viewing angle 90°</i>
3010090	AVS-Camera-KU 115° FHD	▪ Bildwinkel 115°	▪ <i>Viewing angle 115°</i>

Key Facts

- **Auflösung** 1920x1080
 - **Bildsensor** CMOS 1/2.9"
 - **Gegenlichtkompensation** Automatisch
 - **Spannungsversorgung** 12V DC
 - **Stromverbrauch** ca. 200mA
 - **Bildwinkel** 40°, 70°, 90 & 115° erhältlich
 - **Beleuchtung** 0.1 Lux (Tag), 0 Lux (mit IR 3-5Meter)
 - **Schutzklasse** IP68/IP69K
 - **FPS** 25/30
 - **Betriebstemperaturbereich** -20°C bis +70°C
 - **Lagertemperaturbereich** -40°C bis +85°C
 - **Vibration** 10g
 - **Anschlusskabel** 0,9 Meter
 - **Gewicht** 0,26kg
- **Resolution** 1920x1080
 - **Image Sensor** CMOS 1/2.9"
 - **Backlight compensation** Automatic
 - **Power supply** 12V DC
 - **Power consumption** ca. 200mA
 - **Viewing angel** 40°, 70, 90 & 115° available
 - **Lightning** 0.1 Lux (Day), 0 Lux (with IR 3-5Meter)
 - **Protection class** IP68/IP69K
 - **FPS** 25/30
 - **Operating temperature** -20°C to +70°C
 - **Storage temperature** -40°C to +85°C
 - **Vibration** 10g
 - **Cable** 0,9 Meter
 - **Weight** 0,26kg

Stecker / *Connector*

GX-12 aviation 4p - Buchse, IP67
GX-12 aviation 4p - Female, IP67





